

Product Instructions

Budget Bubble Tube



Product Contents

- Wooden Base with Plastic Shroud
- Clear Acrylic Column
- Cap
- Power Supply

Key Information

Each Budget Bubble Column consists of a wooden base with a plastic shroud and a clear acrylic column.

Only use with the power supply provided.

Assembly Instructions

1. Remove the white plastic cap found at the top of the column.
2. Remove the safety packaging found inside the top.
3. Fill the column with de-ionised water.
4. Replace and re-secure the cover.
5. Place the power supply into the unit base.



Product Instructions

Budget Bubble Tube



How to Use

Once assembled your Bubble Tube can be turned on/off at the mains socket.

The colour of the lights will change automatically cycling through the colour spectrum.

IMPORTANT: After turning the power off, please wait 30 seconds before turning it back on again, to ensure all microcontrollers are completely reset.



Maintenance & Cleaning

The water inside the Bubble Column will naturally become contaminated by dust particles and bacteria in the air; because of this, the column's water should be changed **every four weeks**.

Draining and replacing the water in a Bubble Tube is a simple task. **We recommend filling your tube with de-ionised water.**

Tap water **should not** be used even in small amounts.

Cleaning

- The column will have to be topped up with water as evaporation occurs.
- Always disconnect from the mains before emptying and cleaning the Bubble Column.
- Use a mild detergent and a soft cloth to clean the inside of the tube. Rinse thoroughly before refilling for use.